



Commercial And Industrial Rotationally Molded Brine And Storage Tanks

Commercial and industrial water softeners require a large volume of brine during each regeneration. From a capacity of 65 gallons to 500 gallons our Rotationally Molded Brine Tanks are built to last. Molded out of durable, chemically resistant high density polyethylene, their 1/4" seamless walls won't bulge. All tanks are black, cover included. Rotationally Molded Brine Tanks are strong enough to handle your toughest brine requirements.

| Tank Size | Order No. | Diameter (Inches) | Height (Inches) | Salt Capacity (Pounds) | Volume (Gallons) | Weight (Pounds) |
|-----------|--------------|-------------------|-----------------|------------------------|------------------|-----------------|
| 20 x 48 | G22048CB1P00 | 20 | 48 | 600 | 65 | 29 |
| 24 x 48 | G22448CB1P00 | 24 | 48 | 800 | 95 | 34 |
| 30 x 48 | G23048CB1P00 | 30 | 48 | 1200 | 145 | 53 |
| 39 x 48 | G23948CB1P00 | 39 | 48 | 2200 | 250 | 70 |
| 39 x 60 | G23960CB1P00 | 39 | 60 | 2700 | 300 | 83 |
| 42 x 60 | G24260CB1P00 | 42 | 60 | 3100 | 350 | 97 |
| 50 x 60 | G25060CB1P00 | 50 | 60 | 4500 | 500 | 113 |

Note:

1. Tank sizes 20 through 42 inches in diameter include a carton. The 50 x 60 tank is shrink wrapped only.

Clack Corporation



4462 DURAFORM LANE PO BOX 500 WINDSOR, WI 53598-0500 USA
 PHONE (608) 846-3010 FAX (608) 846-2586 SALES/CUSTOMER SERVICE FAX (800) 755-3010

Form No. 1837
 Updated 12/91